

No.	DATE	MODIFICATION	REASON	MOD. BY
0	09/12/11	Edited in new format.	CAD software change.	E.V.
1	11/03/21	Updated standard.	---	A.U.

# MARKINGS:

LOT (month & year)  
FORGER MARK



& REFERENCE

②

①

Lot and  
Forgeur Mark

16

54

140

67

37

RC16P

Reference  
and Logo

Ø 17,5

Ø 40

## SECTION A-A

DIMENSIONS OF SOCKET COUPLING  
ACCORDING TO IEC-60120 N16 STANDARD



INDUSTRIAS  
ARRUTI S.A.

F40513

NAME

DRAWN BY

E.V.

SIGNED BY

I.L.

2	1	STANDARD SAFETY PIN FOR N-16 BALL SOCKET	STAINLESS STEEL	3196	IEC 372	0.02
1	1	SM SOCKET EYE	GALVANIZED STEEL	0036s	EN-10.083-2	0.87
No.	QTY.	DESCRIPTION	MATERIAL	CODE	STANDARD	WEIGHT (Kg.)
		UNITS (mm.)	TOTAL WEIGHT: 0.89 Kg.			
			- Manufactured according to IEC 61284 standard - Tolerances unless otherwise stated to be: Up to and including 35 mm. ±0.7 mm. Over 35 mm. ±2% - Hot dip galvanized according to ISO 1461 standard - M.B.S.L.: 12.500 daN - M.D.S.L.: 75% M.B.S.L. - lcc: Depend of the connexion to the piece - Coating thickness. Local: 70µm. Average: 85µm			
SOCKET EYE			SCALE	DRAWING	ISSUE	
RC-16-P/16			3:4	0035-M	5	

This drawing is property of I. Arruti and must not be copied, exhibited or furnished without the written consent of I. Arruti.