

No.	DATE	MODIFICATION	REASON	MOD. BY
0	11/12/12	Edited in new format.	CAD software change.	E.V.
1	15/07/15	TC-16/400, eliminate.	TC-16/400, eliminate.	X.E.
2	11/01/19	TC-16/225, is added.	New design	E.V.

MARKINGS:

REFERENCE	CODE	COTE "L" (mm.)	COTE "B" (mm.)	WEIGHT (kg.)
TC-16X40	2833	40	40	0,36
TC-16X100	2842	100	50	0,45
TC-16X160	2213	160	50	0,55
TC-16X225	13273	225	160	0,65
TC-16X250	2215	250	160	0,69
TC-16X340	1471	340	160	0,83

5	1	STAINLESS STEEL 4,5x37 SAFETY PIN	STAINLESS STEEL	0027	-	0.00
4	1	FLAT WASHER METRIC 16	GALVANIZED STEEL	0048	DIN-125	0.01
3	1	SPRING WASHER METRIC 16	GALVANIZED STEEL	0184	DIN-127 B	0.01
2	1	NUT METRIC 16+0.6	GALVANIZED STEEL	0025	DIN-934	0.03
1	1	EYE BOLT	GALVANIZED STEEL	TC16	EN-10083-2	0.00
No.	QTY.	DESCRIPTION	MATERIAL	CODE	STANDARD	WEIGHT (Kg.)

 INDUSTRIAS ARRUTI S.A.		UNITS (mm.) 		- Manufactured according to IEC 61284 standard - Tolerances unless otherwise stated to be: - Up to and including 35 mm. ± 0.7 mm. Over 35 mm. $\pm 2\%$ - Hot dip galvanized according to ISO 1461 standard		- M.B.S.L.: 5.000 daN - M.D.S.L.: 70% M.B.S.L. - lcc: Depend of the connexion to the piece - Coating thickness. Local: 40μm. Average: 50μm		TOTAL WEIGHT: Table	
F40513	NAME			EYE BOLT TC-16xL		SCALE	DRAWING	ISSUE	
DRAWN BY	E.V.		11/12/2012			1:1	TC16-M	1	
SIGNED BY	I.L.		11/12/2012						