o. DATE	MODIFICATION	REASON	MOD. B'
12/01/12		CAD software change.	E.V.
11/03/21	Standard updated.		A.U.
MARKIN LOT (mor	GS: th & year)	Lot and Forgeur MArk  \$\overline{\phi} 20 \mathred{P} \times 48	
	65	DIMENSIONS OF SOCKE ACCORDING TO IEC-60120	N20 STANDARD
<i>_</i> ^	2 1 STANDARD SAFETY PIN FOR N	N-20 BALL SOCKET STAINLESS STEEL 0125	AISI 304 0
77/\	1 1 SM SOCKET EYE		N-10.083-2 1
	.   .   .   .   .   .   .   .   .   .	0,12,7,11,1222 01222   01000	

///\	\ [	1	1	SM SOC	KET EYE		GALVANIZED STEEL 0		01358	S EN-10.083-2		1.38	
		No.	QTY.		DE	SCRIPTION	MATERIAL		CODE	STAN	DARD	WEIGH	HT (Kg.)
INDUSTRIAS		ι	JNITS	(mm.)		ed according to IEC 61284 stan unless otherwise stated to be:	dard	- M.B.S.L.: 18.000 daN - M.D.S.L.: 75% M.B.S.L.					
ARRUTI S.A.		-	7	<b>—</b>	Up to and including 35 mm. ±0.7 mm. Over 35 mm Hot dip galvanized according to ISO 1461 standa			±2% - Icc: Depend of the connexion to the piece					
F40513	NAME		_	<u> </u>	- Hor dip gaiv	ariizea according to iso 14013	idildala	- Coding micki	C33. LOC	ui. 70µi	II. AVEIU	ge. 00p	1111
DRAWN BY	E.V.				12/01/2012	SOCKET EYE R-20-P/21			SC	CALE	DRAW	VING	ISSUE
SIGNED BY	I.L.				12/01/2012				3	3:4	0134	1-M	4